

# ACTIVE<sup>®</sup> PRO



Sports Flooring	Characteristics	Standards	Units	ACTIVE <sup>®</sup> PRO
Product Chemistry	VOC, Indoor Air Quality	CA Section 01350	Floorscore Certified	Yes
	Heavy Metal Free	ASTM F963	Classification	<0.25ppm, Pass
	Phthalate-Free	ASTM F3414	Classification	<1.0ppm, Pass
Product Classification	PVC Sports Flooring	ASTM F2772	Indoor Sports Floor	Class 2, A
		EN 14904		Type 1
	Wear Layer	ASTM F1303/F410	Classification	Type 1 - Grade 1
Description	Thickness	EN 428	mm	7.00
	Weight	EN 430	grams / m <sup>2</sup>	4350
			lbs/sq ft	0.89
	Width	EN 426	meter	1.80
			feet - inches	5 feet 11 inches
	Standard Roll	EN 426	meters	20.00
			feet - inches	65 feet 7 inches
	Extra Long Roll	EN 426	meters	26.00
feet - inches			85 feet 4 inches	
Sports Properties	Force Reduction	ASTM F2772	Classification	Class 2
	Vertical Deformation	ASTM F2772	Classification	Class A
		EN 14809	Classification	Type 1
	Ball Rebound	ASTM F2772	Classification	Pass
		EN 12235	Requirement (>90%)	Pass
	Surface Finish Effect	ASTM F2772	Classification	Pass
		ISO 2813 Gloss	Classification	Pass
	Resistance to Indentation	EN 1516	Requirement (<0.5mm)	Pass
	Force Reduction (Athletic Use)	ASTM F2569	Avg.Drop	>25%, Pass
	Shock Absorption	EN 14808	Classification	Type 1
Rolling Load Indentation	EN 1569	Classification	Pass	
Resistance to Impact	EN 1517	Classification	Pass	
Pendulum Test	EN 13036-4	Requirement (80-110)	Pass	
Technical Characteristics	Surface Frictional Property	ASTM E303	BPN Dry	BPN>85
	Abrasion Resistance	EN ISO 5470	CS-10 @ 1000 cycles	Pass
			H-18 @ 1000 cycles	Pass
	Critical Radiant Flux	ASTM E648	Classification	Class 1
	Chemical Resistance	ASTM F925	Classification	Excellent
	Static Load Limit	ASTM F970	Load - 175 lbs	Pass
	Reflectance	EN 13745	Report	LRV 45
Color Fastness to Light	ISO 105 B02	Rating	>#7	

ISO 9001 ISO 14001 ISO 18001

