

**Capilla®**

Wall Covering



Characteristics	Standards	Units	Capilla®
Type of wall covering	EN 15102	Classification Norm	Vinyl Wall Covering
Special treatment			PUR
Overall thickness	ISO 24346 - EN 428	mm	1.0 mm
Weight	ISO 23997 - EN 430	g/m <sup>2</sup>	5000
Size	ISO 24341 - EN 426	mm	2800 x 1220
Dimensional stability	ISO 23999 - EN 434	%	≤ 0.40
Flexibility	ISO 24344 - EN 435	20mm mandrel	< 20
	ASTM F137		Pass
Seam Strength	ISO 16906	N/50mm	Pass
Residual indentation	ISO 24343 - 1 - EN 433	mm	≤ 0.10
Colour fastness to light	EN ISO 105 - B02	Degrees	≥ 6
	ASTM F1515	ΔE ≤ 800 after 300 hours (colour change)	Pass
Heat Stability	ASTM 1514	ΔE ≤ 0.80 (colour change)	Pass
Reaction to fire	EN 13501-1 : 2007+A1	Class	Bfl - S1
	ASTM E 648	Type	1
Smoke density	ASTM E 662	Dm	< 450
Stain & chemical esistance	ISO 26987 - EN 423	Index	0 (Excellent resistance)
	ASTM F925	Resistance	Pass
Fungi & bacteria resistance	ISO 846 A, C		Does not favour growth

